

SPECIFICATION

BUCKLEY ACCESS DOORS

DUCT ACCESS DOORS

- A. Provide 1" Insulated Access Doors in Ducts at each automatic or motor-operated Damper, Fire Damper, at all main trunk duct manual Dampers, and at fresh air, exhaust air and other major manual Dampers. Access Doors shall be Buckley Model C-10 (Double Cam) or H-10 (Single Cam and Hinge) as manufactured by **Buckley Associates Sheet Metal Workers Local 17. (1-781-878-5000)**
- B. Access Door Panels shall be constructed from 24 Gauge Galvanized Steel (22 gauge on 14 x 14 and larger). Both sides of the Door will have 1/8" Neoprene gaskets to prevent leakage. Half-inch Access Doors or those without gaskets on both sides of the Door are unacceptable.

*To maintain Buckley's policy of continuous improvement, we reserve the right to change prices, specifications, ratings or dimensions without notice or obligation. **Manufactured by Sheet Metal Union Local 17.***

MANUFACTURED BY: BUCKLEY ASSOCIATES, INC., HANOVER, MA

MAIN OFFICE

HANOVER, MA
Phone (781) 878-5000
Fax (781) 871-9435

SALES AND WAREHOUSES

NEWINGTON, CT
Phone (860) 666-0555
Fax (860) 666-3035

MANCHESTER, NH
Phone (603) 669-3566
Fax (603) 669-2347

ALBANY, NY
Phone (518) 438-7423
Fax (518) 438-5527



Visit us on the World Wide Web at: <http://www.buckleyonline.com/>

97423