

SPECIFICATION

BUCKLEY SPIN-IN FITTINGS

- A. Contractor shall provide Buckley Spin-In Takeoffs at all branch duct locations. The Spin-In connector shall be Type M (no Damper) or Type MD (with Damper) and shall be manufactured by Buckley Associates (781-878-5000) **Sheet Metal Workers Local 17**.
- B. Spin-In Connector shall be manufactured of 26 Gauge Galvanized Steel.
- C. Model MD (with Damper) shall have a standard Single Blade 26 Gauge Damper. Damper hardware is to be Type K-708 (spring bearing) and Type K-900 (threaded fixed tip) with Neoprene Gasketed Washer on K-900, to prevent air leakage through side Damper holes.

*To maintain Buckley's policy of continuous improvement, we reserve the right to change prices, specifications, ratings or dimensions without notice or obligation. **Manufactured by Sheet Metal Union Local 17.***

MANUFACTURED BY: BUCKLEY ASSOCIATES, INC., HANOVER, MA

MAIN OFFICE

HANOVER, MA
Phone (781) 878-5000
Fax (781) 871-9435

SALES AND WAREHOUSES

NEWINGTON, CT Phone (860) 666-0555 Fax (860) 666-3035	MANCHESTER, NH Phone (603) 669-3566 Fax (603) 669-2347	ALBANY, NY Phone (518) 438-7423 Fax (518) 438-5527
---	--	--



Visit us on the World Wide Web at: <http://www.buckleyonline.com>

97469