


BELLMOUTHS

Spun Bellmouth with Gasket

MATERIALS AVAILABLE:

Galvanized Paintgrip, Aluminum, Stainless Steel Available with factory installed volume damper
Available up to 48"



DIMENSIONS						
(A)	(B)	(R)	(F)	(H)	(S)	Weight
4"	8"	1.0"	1"	3"	2"	1.0 lbs
5"	9"	1.0"	1"	3"	2"	1.25 lbs
6"	10"	1.0"	1"	3"	2"	1.50 lbs
7"	10"	1.0"	1"	3"	2"	1.75 lbs
8"	11"	1.0"	1"	3"	2"	1.95 lbs
9"	12"	1.0"	1"	3"	2"	2.25 lbs
10"	13"	1.0"	1"	4"	2"	2.5 lbs
12"	15"	1.0"	1"	4"	2"	3.0 lbs
14"	17"	1.0"	1"	4"	2"	3.5 lbs
16"	19"	1.0"	1"	5"	2"	4.0 lbs
18"	21"	1.0"	1"	5"	2"	4.5 lbs
20"	24"	1.0"	1"	5"	2"	5.0 lbs
22"	25"	1.0"	1"	5"	2"	5.5 lbs
24"	28"	1.0"	1"	5"	2"	6.0 lbs

KEY:

A=Opening dimension 1/8" under nominal size

F = 1"

H = Height

R = Radius

B = Flange side

S=2"