Submittal Data

Buct Duct Aluminum Silencer

Construction Features

Buckley's Buck Duct Aluminum Silencer is comprised of an all-aluminum perforated core with an open area of 20-25%. The perforated inner duct is enclosed in a 2" thick fiberglass insulation. The outer jacket consists of Triple-Lock Aluminum Flexible Duct that is corrugated with mechanical interlocking seams to form an air tight, flexibal, metal duct. The end fittings are factory installed.

Technical Data

Standard Lengths (Feet)
E-96-66, Procedure A
UL Listing
Minimum Burst Pressure2 ½ times working pressure Operating Temperature Range60° to +250° F Flame SpreadLess than 25 Smoke DevelopedLess than 50 R-Value





Noise Reduction db (5' ft length, 8" inch diamater)

Octave Band	2	3	4	5	6	7	8
HZ	125	250	500	1000	2000	4000	8000
Model BDS Buck Duct Aluminum Silencer	+2	-3	-12	-23	-17	-7	-7

About Our Tests

Our tests were conducted by Energistics Laboratory, an independent research development facility. All testing and rating procedures used by the laboratory are accordance with ARI, ADC, ISO, and ASHRAE standards as applicable. The results of the testing are based on test results of sound collected on various types of eight-inch round Buck Duct specimens. Each test sample was tested at a velocity of 500 FPM and was then compared to hard metal duct at the same velocity. For the purpose of these tests, the only comparison made is test specimens to hard duct.



